

XT-4F TOUCH BUTTON

XT range

The nexmosphere X-Touch range is a family of touch button boards in various sizes and configurations that can be combined in one setup. The X-touch technology enables button placement hidden inside the display structure for seamless, non visible integration into the application. The technology works with multiple surface materials, such as acrylic, glass, carton, and wood. The button sensitivity and responsiveness can be adjusted by programming the Xperience controller accordingly.



The X-Touch 4F is a linear board with four small sized capacitive touch buttons.

Features

- 4 small-sized capacitive touch buttons (16 mm)
- 4 bright controllable LED's (W-version only)

X-touch technology

- Works with multiple materials, such as acrylic, glass, carton, stone, and wood
- Compatible with any nexmosphere Xperience controller
- Powered and programmable by nexmosphere Xperience controller

Benefits

- Ultra flat (4 mm), easy to integrate
- 4 bright white indication LEDs (custom colors on request)
- 4 programmable options for LED output; on, off, slow, and fast blink
- Multiple data gathering functionalities on Xperience controller offer unique insight into how your application is being used
- Auto-calibration and auto-start for highly reliable applications (24/7)

X-talk

The X-Touch boards can easily be connected to any of the nexmosphere Xperience controllers using the X-talk interface. All settings of the X-Touch are programmable on the controller, enabling a seamless integration in your application.

- Plug and smile interface
- Compatible with any nexmosphere Xperience controller
- Powered and programmable by nexmosphere Xperience controller

XT-4F TOUCH BUTTON

Mounting specifications

- Keep clean from metal objects or surfaces
- Maximum material thickness: 1–6 mm, depending on the material
- Works on glass, acrylic, wood, cardboard, stone, and non-metallic materials

Thermal specifications

Operating temperature: +10°C...+40°C/ +50°F ... +104°F
 Storage temperature: -20°C...+50°C/ -4°F ... +122°F

Electrical specifications

- Operating voltage: 5V DC (via X-talk interface)
- Power consumption: 40mA

Miscellaneous

- Mounting holes for easy fixation
- Customized layouts and board shapes available on request
- 1-year warranty (optional 3-year extended warranty available)

Packaging

Items per carton 1, 10 or 50 pcs


Standards and Certifications



RoHS
compliant


Mechanical dimensions

LxWxH: 122 x 30x 3.4 mm
 Screw fixation: 25 / 50 / 25 x 20 mm



Interfaces

1. Touch button 1 and button LED 1 (W-version only)
2. Touch button 2 and button LED 2 (W-version only)
3. Touch button 3 and button LED 3 (W-version only)
4. Touch button 4 and button LED 4 (W-version only)



Ordering information

Product ID	Description	Quantity
XT-4FW4	X-Touch, 4 small button, Linear, White LED, 60cm cable	1 pc
XT-4FW5	X-Touch, 4 small button, Linear, White LED, 120cm cable	1 pc
XT-4FW6	X-Touch, 4 small button, Linear, White LED, 180cm cable	1 pc
XT-4FN4	X-Touch, 4 small button, Linear, No LED, 60cm cable	1 pc
XT-4FN5	X-Touch, 4 small button, Linear, No LED, 120cm cable	1 pc
XT-4FN6	X-Touch, 4 small button, Linear, No LED, 180cm cable	1 pc

Nexmosphere

High Tech Campus 10 (Mμ building)
 5656 AE Eindhoven • The Netherlands

T +31 40 240 7070
 E sales@nexmosphere.com

© 2017 Nexmosphere. All rights reserved. v1.0 / 11-18
 All content contained herein is subject to change without prior notice.